

OUTDOOR-14YD-DIESEL-TRI-Euro 2-



Non contractual photo

**Dimensions :**

L : 2050 mm

I : 1050 mm

H : 1240 mm

Weight : 1045 kg

1. GENERAL TECHNICAL DESCRIPTION - PRO20592

GENERAL DATAS

PRP Prime Rated Power	12,5 kVA/9,6 kW
ESP Emergency Standby Power	13,8 kVA/10,4 kW
Voltage	230 400 V
Power factor (cosΦ)	0,8
Rotation speed	1500 rpm

Frequency	50 Hz
Number of phases	3
Acoustic pressure level at 7m	< 60 dB(A)
Fuel tank autonomy at 75%	56 h
Fuel tank capacity	100 L

ENGINE

Model	YD480D
Number of cylinders	4
Governor type	Mechanical
Specifications	4 stroke cycle engine, direct fuel injection, liquid-based cooling
Displacement	1,8L
Maximum standby power at rated rotation 1500 tr/min	14 kW
Engine starting type	Electrical 12 V
Consumption à 75%	1,79 L/h

ALTERNATOR

Amperage	18,1 A
Technology	Brushless, With Electronic Regulation
Voltage regulation type	Electronic
IP code	23
Insulation class	H

CIRCUIT BREAKER

Type	Four poles thermal magnetic circuit breaker with adjustable differential switches
-------------	---



The ergonomic design of the control panel enables access to all main functions quickly and easily :

- Mechanical hour meter
- DEEP SEA control panel
- Alarms
- Manual/Automatic starting
- Main circuit breaker...




2. EQUIPEMENT

1. Socket box

Integrated, non-protruding socket box equipped with circuit breakers with differential protection for each socket A 4 pole thermo-magnetic circuit breaker with earth leakage protection secures the equipment.

Détails :

- 1 5 pole 32A socket (IP55)
- 1 5 pole 16A socket (IP55)
- 1 3 pole 16A socket (IP44)



2. DSE 7320 MKII Control panel



The DSE7320 MKII is a powerful Automatic Mains Failure generating set control panel with a sophisticated range of new features.

Equipped with a new Dual Core processor and extended memory, this module offers faster, more powerful processing power, faster operational responses in intensive applications and increased functionality, with the installation of a data logger.

By monitoring a higher number of engine parameters, the module displays warnings, shut-downs and information on engine status on the backlit LCD screen, on remote PC's and via SMS (with a remote communication device).

3. Why to choose a "GELEC OUTDOOR"

- Single point lift
- 1 Battery isolator
- 2 three way valves for external tanks
- 1 manual drain pump
- 1 busbar
- Mechanical hour meter
- Supply "charge safety"

