




OUTDOOR-150YC-DIESEL-TRI -Euro 3-



Non contractual photo



Dimensions :

L : 3 500 mm

I : 1 300 mm

H : 1 860 mm

Weight : 2 850 kg

1. GENERAL TECHNICAL DESCRIPTION - PRO20603

GENERAL DATAS

PRP Prime Rated Power	138 kVA/110,4 kW
ESP Emergency Standby Power	150 kVA/120 kW
Voltage	400V
Power factor (cosΦ)	0,8
Rotation speed	1 500rpm

Frequency	50Hz
Number of phases	3
Acoustic pressure level at 7m	< 65dB(A)
Autonomy at 75% load	15 h
Fuel tank capacity	270L

ENGINE

Model	YC6A190-D30
Number of cylinders	6
Governor type	Electronic
Specifications	4 stroke cycle engine, common rail injection , liquid-based cooling
Displacement	7,252L
Maximum standby power at rated rotation 1500 tr/min	138 kW
Engine starting type	Electrical 24 V
Fuel consumption à 75%	18,40 L/h

ALTERNATOR

Amperage	180,60 A
Technology	Brushless, With Electronic Regulation
Voltage regulation type	Electronic
IP code	23
Insulation class	H

CIRCUIT BREAKER

Type	Four poles thermal magnetic circuit breaker with adjustable differential switches
------	--



The ergonomic design of the control panel enables access to all main functions quickly and easily :

- Mechanical hour meter
- DEEP SEA control panel
- Alarms
- Manual/Automatic starting
- Main circuit breaker...



OUTDOOR-150YC-DIESEL-TRI -Euro 3-

2. EQUIPEMENT

1. Socket box

Integrated, non-protruding socket box equipped with circuit breakers with differential protection for each socket A 4 pole thermo-magnetic circuit breaker with earth leakage protection secures the equipment.

Specifications :

- 1 5 pole 125A socket (IP67)
- 1 5 pole 63A socket (IP67)
- 4 5 pole 32A socket (IP55)
- 1 3 pole 16A socket (IP44)



2. DSE 7320 MKII Control panel



The DSE7320 MKII is a powerful Automatic Mains Failure generating set control panel with a sophisticated range of new features.

Equipped with a new Dual Core processor and extended memory, this module offers faster, more powerful processing power, faster operational responses in intensive applications and increased functionality, with the installation of a data logger.

By monitoring a higher number of engine parameters, the module displays warnings, shut-downs and information on engine status on the backlit LCD screen, on remote PC's and via SMS (with a remote communication device).

3. Why to choose a "GELEC OUTDOOR"

- Single point lift
- 1 battery isolator
- 2 three way valves for external tanks
- 1 manual drain pump
- 1 busbar
- Mechanical hour meter
- Supply "charge safety"

The YC Euro 3 engines are equipped with a BOSCH Common Rail injection system

